

American Access Industries and Services

AVPL Vertical Lift Order Form

Date _____

Dealer Information:

Dealer Account # _____

Dealer Name: _____

Job Information

Job Name: _____

Installation Address: _____

Shipping Address: _____

We ship by FedEx Freight or SAIA

Drawings:

_____ Do not manufacturer until custom presentation drawings are approved and returned.

_____ Quote only.

Drawings will be sent by e-mail.

E-mail Address _____

_____ Process order without presentation drawings.

Miscellaneous:

Ordered by _____

Received by _____

December 3, 2019

Standard Equipment:

Rated load: 750 lbs. (340 kg.)

Speed with rated load 20 fpm. (.04 ms.)

Removable base and lift weldment.

Maximum number of stops: 3

Power supply: 120 vac. 60Hz, 15 amp.

Finish Grey/White powder coat. Consult the sales dep. about other RAL colors.

ETL Listed.

Hydraulic Battery operated.

Motor controller: Relay logic.

Constant Pressure 24vdc controls.

Internal Battery Disconnect.

42" high guard panels

Grab Rail.

Non-skid surface platform 36" X 48" inside dimension.

Manual pull cable lowering device.

Broken chain safety device.

Modular tower AVPL 72 and taller.

Warranty:

3 years on pump and cylinder

2 years on all other components.

Unit is manufactured to A18.1-2017 national code.

If local code deviates from the A18.1-2017. Contact the sales department to see if we can accommodate your local requirements.

Lifting Height

Measure the EXACT lifting height. Measurement must be a vertical line taken from the top landing to the bottom landing. For pit mount units, measure from the bottom of the pit. Check the appropriate line and indicate the type of mounting.

Upper landing exact lifting height. _____

(Note: An upper landing gate will add 5/8" to the lift height)

If unit is to be a 3 stop note exact Mid floor height _____

_____ Pit mount

_____ Floor mount _____ Add fixed ramp.

_____ Add Mechanical Auto ramp.

_____ Add Power Auto ramp.

_____ Hoistway installation. _____ Include fixed ramp.

Model

_____ AVPL 50 Max lift height 53"

_____ AVPL 72 Max lift height 75"

_____ AVPL 96 Max lift height 99"

_____ AVPL 120 Max lift height 123"

_____ AVPL 144 Max lift height 147"

Controls

_____ 2 Stop unit (Standard)

_____ 3 Stop unit

Platform

_____ 36" X 48" Straight through (Standard)

_____ 36" X 60" Straight through

_____ Enter/Exit Panel

_____ 36" X 60" 90 Deg. RH Platform

_____ 36" X 60" 90 Deg. LH Platform

_____ Safety Pan on Platform

Location

_____ Indoor unit

_____ Outdoor unit

Platform Options

_____ Keylock Removable off only

_____ Keylock Removable on and off

_____ Paddle control

_____ Electric Eyes Single Opening

_____ Electric Eyes 2 Openings

_____ Telephone jack on platform

_____ Telephone jack and phone on platform

_____ ADA phone on platform

_____ Emergency light on platform

_____ Emergency Stop on platform

_____ Emergency Stop and Alarm on platform

Bottom Landing Options

Call _____ Flush/Surface mount call

_____ Frame mount call (Non-Fire door only)

_____ Keylock Removable off only

_____ Keylock Removable on and off

_____ Paddle control

_____ Wireless calls (Must be on all floors)

Bottom Door Options

_____ 6'8" Flush mount 1-1/2hr. Fire rated door with Von Duprin strike.

_____ 6'8" Flush mount 1-1/2hr. Fire rated door with Honeywell Interlock.

_____ Non-Fire rated door _____ Clear _____ Bronze

_____ Von Duprin Strike and Dead latch for door by others. _____ Wood frame _____ Steel frame

_____ Honeywell Interlock for door by others.

_____ Platform gate

_____ Add Clear plex to Platform gate

_____ Add Bronze plex to Platform gate

_____ Doors By Others

_____ Auto door opener

_____ Add relay for auto door opener by others

Mid Landing Options

- Flush/Surface mount call
- Frame mount call (Non-Fire door only)
- Keylock Removable off only
- Keylock Removable on and off
- Paddle control
- Wireless calls (Must be on all floors)

Middle Door Options

- 6'8" Flush mount 1-1/2hr. Fire rated door with Von Duprin strike.
- 6'8" Flush mount 1-1/2hr. Fire rated door with Honeywell Interlock.
- Non-Fire rated door Clear Bronze
- Von Duprin Strike and Dead latch for door by others. Wood frame Steel frame
- Honeywell Interlock for door by others.
- Doors by others
- Auto door opener
- Add relay for auto door opener by others

Draw in tower location.

Draw in and note upper and lower gate swing direction.



Top Landing Options

- Flush/Surface mount call
- Frame mount call (Non-Fire door only)
- Keylock Removable off only
- Keylock Removable on and off
- Paddle control
- Wireless calls (Must be on all floors)

Top Door Options

- 6'8" Flush mount 1-1/2hr. Fire rated door with Von Duprin strike.
- 6'8" Flush mount 1-1/2hr. Fire rated door with Honeywell Interlock.
- Non-Fire rated door Clear Bronze
- Von Duprin Strike and Dead latch for door by others. Wood frame Steel frame
- Honeywell Interlock for door by others.
- Landing gate
 - Add Clear plex to Landing gate
 - Add Bronze plex to Landing gate
- Doors by others
- Auto door opener
- Add relay for auto door opener by others

Draw in tower location and middle landing door swing direction and location.



Miscellaneous Options

_____ Remote emergency lowering key switch

_____ Pit switch on tower

_____ Pit switch mounted by installer

_____ Emergency lights on calls (must have e-lights on platform).

_____ Fire Sign "In case of fire do not use lift" 1 per floor

Special RAL color (Ask Sales Dept).